

### Posts

Post system for flat panels.

Two fixings systems are available: with clamps or with U-covering plate

### Product detail



### BENEFITS

- 2 fixing systems available
- mounting support

#### Profile

- Welded rectangular posts
- Cross section of the post: 60 x 40 mm
- Plate thickness: 1.5 – 2 mm
- Hard plastic cap
- I/V: 5.00 cm<sup>3</sup> (for plate thickness: 1.5 mm) or I/V: 6.19 cm<sup>3</sup> (for plate thickness: 2.0 mm)
- Inserts in M8

#### Accessories

- Clamps
- U-covering plate
- 1 mounting support in steel on top of the post
- Base plate (welded)
- Security bolts M8 x 40
- Bent arms
- Corner clamps



#### Coating technique

Galvanised in-and outside (275 g/m<sup>2</sup> - both sides combined) and plastic coated (min. 60 micron)



#### Colours

D-LOX posts are standard available in galvanised execution, in green (RAL 6005) and metallic anthracite (BF7016M). Other RAL colours are available upon request.

#### D-LOX<sup>®</sup> POSTS

Panel height mm	Post section mm	Post length mm	Number of clamps per post
630	60 x 40 x 1.5	1000	3
830	60 x 40 x 1.5	1300	3
1030	60 x 40 x 1.5	1500	4
1230	60 x 40 x 1.5	1700	4
1430	60 x 40 x 1.5	2000	4
1630	60 x 40 x 1.5	2200	5
1830	60 x 40 x 2	2400	5
2030	60 x 40 x 2	2600	5
2230	60 x 40 x 2	3200	6
2430	60 x 40 x 2	3000	6

### Compatible products

- Nylofor 2D
- Nylofor F

